



Mactac

Digital Quick Portfolio Guide

Overlamine Products

(2/2)

Application	Product name	PVC FREE	Caliper (µm)	Front film: Color and Finish						Adhesive	Liner	Durability*	Conform-ability	Outdoor application	Fire certification EN 13501-1
				Clear	Glossy	Matt	Satin	Optically clear	Textured	Permanent	UV inks compatible	Type			
Floor Graphics**															
Short term floor application	LUV 6300		125	●	●			●	●	●	CK	6 mths	1D		Bfl-s1
	LUV 6301		100	●	●			●	●	●	CK	3 mths	1D		Bfl-s1
	LUV 6400	●	125	●	●			●	●	●	CK	H: 3 mths/V: 3 yrs	1D		Bfl-s1
	FloorGrip		150	●	●			●	●	●	CK	Indoor: 1yr Outdoor: 3mths	1D	●	Bfl-s1
	StreetLam		385	●			●	●	●	●	CK	6 mths	2D	●	Bfl-s1
Special Laminating films															
Anti-graffiti application	LUV 7036	●	36	●	●			●		●	PET	3 yrs	1D	●	B-s1,d0
	LAG 100	●	60	●			●			●	CK	3 yrs	2D	●	B-s1,d0
Anti-graffiti/ photographs	PG 7075	●	75	●	●			●		●	PET	3 yrs	1D	●	B-s1,d0
Photographics	PG 7285		70	●		●				●	CK	4 yrs	1D	●	C-s1, d0
PermaFun Series	Brushed Metal		100	●					●	●	CK	5 yrs	2D	●	B-s1,d0
	Coarse Wood		120	●					●	●	CK	5 yrs	2D	●	C-s1,d0
Whiteboard application	PG 7034	●	30	●	●					●	PET	2 yrs	1D		na
Mounting films															
Mounting films	PP 2011+	●	12	●						●	SC	5 yrs	1D	●	na
	PP 2018+	●	12	●						●	SC	2 yrs	1D		na

* For more information please refer to the TB 7.5 Outdoor durability of Mactac Graphics self adhesive films

** All Floor Graphics products are EN 13036-4 Anti-slip certified

Think Sustainable!

All paper based packaging elements of our self-adhesive graphics products are 100% recyclable where appropriate paper waste recycling bins are available, and many are already made from recycled content, including inner cores, packaging boxes and plastic core stoppers. Check local recycling guidelines to recycle our packaging!

For more information about Mactac Sustainability commitment please visit the Mactac Graphics website:
www.mactacgraphics.eu/en/about-us/sustainable-graphics-solutions



The mark of
responsible forestry
FSC® C004451

©2023 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

All Mactac statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Mactac products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Mactac products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com> 2023_32054 EN



contact.mactac@mactac.eu | mactacgraphics.eu



Overlamine Products

(1/2)

Application	Product name	PVC FREE	Caliper (µm)	Front film: Color and Finish						Adhesive	Liner	Durability*	Conform- ability	Outdoor application	Fire certification EN 13501-1
				Clear	Glossy	Matt	Satin	Optically clear	Textured	Permanent	UV inks compatible	Type			
Vehicle wrapping															
Long term application on curved surfaces	LF 10700 CG-UV		30	●	●					●	●	CK	6 yrs	3D	B-s1,d0
	LF 10700 CM-UV		30	●		●				●	●	CK	6 yrs	3D	B-s1,d0
	LF 10500 CG		50	●	●			●		●		PET	5 yrs	2D+	B-s1,d0
	Permacolor HORIZon™	●	35	●	●					●		CK	7 yrs	3D	na
Curved surfaces															
Long term application for curved surfaces	LF 9700 CG-UV		80	●	●					●	●	CK	5 yrs	2D	B-s2,d0
	LF 9700 CM-UV		80	●		●				●	●	CK	5 yrs	2D	B-s2,d0
	LF 9500 CG		70	●	●					●	●	CK	4 yrs	2D	B-s1,d0
	LF 9500 CM		70	●		●				●	●	CK	4 yrs	2D	B-s1,d0
Medium term application for slightly curved surfaces	LF 9300 CG-UV		80	●	●					●	●	CK	3 yrs	2D	B-s1,d0
	LF 9300 CM-UV		80	●		●				●	●	CK	3 yrs	2D	B-s1,d0
	LF 9300 CS-UV		80	●			●			●	●	CK	3 yrs	2D	B-s1,d0
Flat to slightly curved surfaces															
Medium term application for slightly curved surfaces	LF 8700 CG-UV		80	●	●					●	●	CK	3 yrs	1D	B-s1,d0
	LF 8700 CM-UV		80	●		●				●	●	CK	3 yrs	1D	B-s1,d0
	LF 8700 CS-UV		80	●			●			●	●	CK	3 yrs	1D	B-s1,d0
Short term application for flat surfaces	LF 8500 CG		70	●	●					●	●	CK	2 yrs	1D	B-s1,d0
	LF 8500 CM		70	●		●				●	●	CK	2 yrs	1D	B-s1,d0

* For more information please refer to the TB 7.5 Outdoor durability of Mactac Graphics self adhesive films

** All Floor Graphics products are EN 13036-4 Anti-slip certified



* For more information please refer to the TB 7.5 Outdoor durability of Mactac Graphics self adhesive films
 ** All Floor Graphics product are EN 13036-4 Anti-slip certified